

KCS TraceME TM-186 / R9A10 GPS / GPRS / SMS module



The TM-186 / R9A10 is a high-end product line member of KCS' advanced TraceME track and trace modules. The TM-186 is targeted for remotely tracing and controlling vehicles and other powered equipment.

The TM-186 is equipped with an intelligent RF-location based positioning solution, which provides locating the vehicle or object quickly and accurate in scenarios where traditional GPS systems are insufficient. It offers multiple connectivity options and server connections.

Key Features

- National telecom & worldwide satellite coverage
 - Quad-band GSM/GPRS
 - UMTS/HSPA (*)
 - GPS
 - Glonass/GPS (*)
- Micro SIM socket
- Low power consumption, down to 100uA.
- Robust aluminum enclosure 90 x 67 x 20mm.
- 4 LEDs for user interaction.
- Excellent Glonass/GPS accuracy, external antenna.
- Integrated 2.45GHz. radio for special functions and peripherals. (*)
 - Long range, over 1 km range, line of sight (*)
- Onboard sensors:
 - 3D accelerometer up to 16g.
 - Temperature sensor ($\pm 0.5^{\circ}\text{C}$)
- Wide operating range: -40°C ... $+85^{\circ}\text{C}$ (Excluding optional LiPo battery Cell).
- Multiple watchdog levels for maximum stability.
- 6 to 31VDC power supply
- 5V / 1A power supply for peripherals
- Versatile interfacing:
 - Digital and analog
 - Bluetooth LE, ANT/ANT+ (*)
 - 4x Serial (3V / RS232)
 - CAN bus / OBD-II (*)
 - RS485 (*)
 - iButton™ / 1-Wire™
 - Cameras
 - LCD Display + keyboard
 - Digital tachograph
 - Passive / active RFID
 - Garmin FMI™
- Event based free configurable module to fit any job; 300+ different events and 4,000+ geozones.
- Remote maintenance. Both firmware and configuration files can be updated over the air.
- Runs local user scripts via .src files.
- User definable SMS commands.
- Supports integration into third party networks.

(*) Optional, please contact sales for more details.

Applications

- Vehicle and boat tracking
- Public transport / Railway industry
- Logistics, M2M
- Security and surveillance
- Remote control and diagnostics
- Anti-theft

Product Summary

Equipped with a state-of-the-art GPS receiver, the TM-186 / R9A10 module provides reliable and accurate navigational data.

All communication is handled effectively by a GPRS/GSM modem (QUAD band version) through GPRS or SMS. In areas without network coverage, position-data and events are stored in memory (up to 120,000 positions). As soon as communication is restored, all information can be transmitted.

The TM-186 / R9A10 module is equipped with external power and battery connection and contains full I/O-connectivity and multiple on-board sensors offering easy integration into many applications.

Optional, the module can be extended with many features (3G modem, 2.45GHz. radio, Bluetooth LE, ANT/ANT+ , iBeacon™) providing easy integration with existing wireless networks. This functionality extension upgrades the module into an intelligent location based positioning solution (LBS) for indoor and outdoor anti-theft applications. A sophisticated 'listen before talk' algorithm makes it practically impossible to locate the module which secures the valuable vehicle or object.

The functionality of the module can be remotely programmed to fit any job. From basic/general functionality to advanced/low-level application specific detailed functionality.

All of the necessary server-side scripts to process and store data from these units are available for registered distributors and resellers. If you do not want to host data and maps yourself, you can use the hosting services of one of our partner companies.

(*) Optional, please contact sales for more details.

Ordering information

- TM-186LAQ Full version
- TM-186BLE Full version + Long-range RF
- TM-186C Full version + CAN or RS485-interface
- (*) Optional, please contact sales for more details

Related products:

- TM-R9B3 Basic version (TM-186 with basic I/O-functionality)

Specifications KCS TraceME TM-186

Data communication

GPRS Modem	Quectel M95 QUAD band, optional UG95(-A or -E) UMTS/HSPA Module, optional UG96 UMTS/HSPA Module, all global certifications and R&TTE directives.
Power saving	Typical power consumption in sleep mode: 1.3mA @ GSM, DRX = 5 1.2 mA @ GSM, DRX = 9 1.15 mA @ UMTS, DRX=9
Frequency bands	<ul style="list-style-type: none"> • Quad-band GSM850, GSM900, DCS1800, PCS1900 • Dual-band UMTS850/1900 or UMTS900/2100 • Five-band UMTS800/850/900/1900/2100 • Frequency bands can be set by AT command • Compliant with GSM Phase 2/2+
GSM Class	Small MS
Transmitting power	<ul style="list-style-type: none"> • Class 4 (2 W) at GSM850 and GSM900 • Class 1 (1 W) at DCS1800 and PCS1900 • Class 3 (250 mW) at UMTS 800/850/900/1900/2100
GPRS connectivity	<ul style="list-style-type: none"> • GPRS multi-slot class 1~12 (configurable) • GPRS mobile station class B

RF Communication (*)

Radio chip	Nordic nRF51422 (*)		
Frequency	Worldwide 2.45 GHz. ISM band, 126 channels, GFSK modulation		
Amplifier	RFaxis RFX2401C		
	Without amplifier	With amplifier	
RF Tx Power	0...-20dBm	+20...0dBm	
RF Rx Sensitivity	2Mbps	-85 dBm (typical)	-90 dBm (typical)
	1Mbps	-90 dBm (typical)	-93 dBm (typical)
	250Kbps	-96 dBm (typical)	-102 dBm (typical)
Ultra low power	13 uA average current use, at 1 RX/TX per second	90 uA average current use, at 1 RX/TX per second, +20 dBm Tx.	

(*) Optional, please contact sales for more details.

Navigation

GPS Receiver	Quectel L70 GPS module, optional L76 GNSS (Glonass + GPS) module	
Frequency	GPS L1 1575.42 MHz. C/A Code, 48 search channels Glonass L1 1598.0625 ~ 1605.375 C/A Code	
Sensitivity	Acquisition	-148 dBm (typical)
	Reacquisition	-160 dBm (typical)
	Tracking	-165 dBm (typical)
Horizontal Position Accuracy	<2.5 m CEP	

Electrical

Power supply	External +6...+31VDC
Charging Current (LiPolymer)	450 mA. Observing 0...+45 °C safety range for LiPolymer.
Typical Power Consumption	20 mA, GPS full power tracking, open GPRS session
	6 mA, using AlwaysLocate™
	100 uA, GPS/GPRS/sensors power down, 4 inputs and 1 timer active

External Connections

External antenna connectors



GSM/GPRS	External GSM/GPRS antenna (*)
GPS	External GPS antenna (*)

(*) Please contact sales for more details.

Optional RF variant (*)



GSM/GPRS	External GSM/GPRS antenna (*)
GPS	External GPS antenna (*)
RF	External 2.45GHz. antenna (*)

(*) Please contact sales for more details.

External Connections

Front view Power and I/O-connectors



Pin	Signal	Type	Description
1	GND for VCC	GND	Ground for VCC
2	VCC	VCC	+6...+31VDC or VCC Charge input
3	GND for I/O	GND	Ground for I/O
4	Digital/Analog_In5	I	Digital/Analog Input 5 (0..31V)
5	TXD1_3V	O	3 Volt serial transmit port 1
6	RXD1_3V	I	3 Volt serial receive port 1, hardware pulse counter
7	TXD2_RS232	O	RS232 serial transmit port 2
8	TXD2_3V	O	3 Volt serial transmit port 2
9	GND for I/O	GND	Ground for I/O
10	I/O1 or RXD4_3V or One-Wire™ or	I/O	I/O1 (3 Volt) - or RXD4 (e.g. Camera1) - or One-Wire™
11	ADC6 I/O2 or TXD4_3V or One-Wire™	O	- or analog input (ADC6) range +0.0...+2.5Volt I/O2 (3 Volt) TXD4 (e.g. Camera1) Note: Connect pins 10-11 for One-Wire™ operation
12	Digital_Out1	O	Open Collector max. 31V /160 mA, protected via Polyswitch fuse
13	Digital_Out2	O	Open Collector max. 31V /160 mA, protected via Polyswitch fuse
14	GND for I/O	GND	Ground for I/O
15	Digital_Out3	O	Open Collector max. 31V /160 mA, protected via Polyswitch fuse
16	Digital_Out4	O	Open Collector max. 31V /160 mA, protected via Polyswitch fuse
17	TXD3_RS232	O	RS232 serial transmit port 3
18	TXD3_3V	O	3 Volt serial transmit output 3
19	RXD3_RS232	I	RS232 receive input 3
20	RXD2_RS232	I	RS232 receive input 2
21	VCC_3V3	VCC	External Supply 3.3V switchable by module
22	N/C	-	Reserved
23	N/C	-	Reserved
24	Digital/Analog_In1	I	Digital/Analog Input 1 (0..31V)
25	Digital/Analog_In2	I	Digital/Analog Input 2 (0..31V)
26	N/C	-	Reserved
27	Digital/Analog_In3	I	Digital/Analog Input 3 (0..31V)
28	Digital/Analog_In4	I	Digital/Analog Input 4 (0..31V)
TM-186C			
E	CAN_H / RS485-A	I/O	CANH or RS485-A
F	CAN_L / RS485-B	I/O	CANL or RS485-B
G	GND for CAN / RS485	GND	Ground for CAN / RS-485

About KCS BV

KCS BV, founded in The Netherlands in 1984, develops and manufactures electronics in-house for industrial applications, medical purposes, broad-casting solutions, etc.

Support

Visit our support page at: www.trace.me

Sales

Contact us by email: trade@trace.me

Final notes & certification

We certify that Kolff Computer Supplies BV, Dordrecht, The Netherlands does not make any hardware or IMEI modifications to the QUECTEL devices as used in the TraceME track & trace device. All software modifications are restricted to official firmware upgrades as provided by Quectel Wireless Solutions Co., Ltd..

KCS is ISO 9001:2008 and ISO 14001 certified since 1999.

WARNING:

- The device should be turned off in vicinity of petrol pumps, chemical, flammable or hazardous environments where ignition of flammable atmospheres is possible.
- The GSM unit and antenna shall be operated at a distance greater than 20 cm from the human body.
- The device is to be operated in accordance with the user instructions or manufactured recommendations.

Disclaimer

KCS BV reserves the right to make changes without further notice to any products herein to improve reliability, function or design. KCS BV does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

©2015 KCS BV
Kuipershaven 22
3311 AL Dordrecht
The Netherlands
Fax 1: +31 (0)78 6312659
Fax 2: +31 (0)20 5248130
email: trade@trace.me
URL: www.trace.me